

Coil Heaters Flexible Connection on each end (RFC CL)



General Specifications

- Stainless steel tube (ANNEALED).
- Connections on each side
- Possibility to manufacture special measures

Quality control

- Insulation: 5 MOhm at 500 V DC Cold (minimum).
- Dielectric strength: 1500 V 1 second.
- Nominal Power: + 5% - 10%

Production Program

6,50 Ø - 8 Ø - 8,50 Ø

COLO ZONE 40mm EACH SIDE, CONNECTION THREADED STUD M2.5

DIAMETER	LENGTH ± 1,5%	POWER 230 V	DIAMETER	LENGTH ± 1,5%	POWER 230 V	DIAMETER	LENGTH ± 1,5%	POWER 230 V
6 Ø ± 0,10	300	315	8 Ø ± 0,10	300	615	8,5 Ø ± 0,10	300	615
	350	385		350	755		350	755
	400	455		400	895		400	895
	450	530		450	1.035		450	1.035
	500	600		500	695 1.175		500	695 1.175
	550	670		550	775 1.315		550	775 1.315
	600	745		600	860 1.455		600	860 1.455
	650	815		650	940 1.595		650	940 1.595
	700	885		700	1.025 1.735		700	1.025 1.735
	750	995		750	1.105 1.875		750	1.105 1.875
	800	1.030		800	1.190 2.015		800	1.190 2.015
	850	1.100		850	1.270 2.155		850	1.270 2.155
	900	1.170		900	1.350 2.295		900	1.350 2.295
	950	1.245		950	1.435 2.435		950	1.435 2.435
	1.000	1.315		1.000	1.520 2.570		1.000	1.520 2.570
	1.050	1.385		1.050	1.600 2.710		1.050	1.600 2.710
	1.100	1.455		1.100	1.680 2.850		1.100	1.680 2.850
	1.150	1.530		1.150	1.765 2.990		1.150	1.765 2.990
	1.200	1.600		1.200	1.845 3.130		1.200	1.845 3.130
	1.250	1.670		1.250	1.930 3.270		1.250	1.930 3.270
1.300	1.745	1.300	2.010 3.400	1.300	2.010 3.400			
1.350	1.815	1.350	2.095 3.550	1.350	2.095 3.550			
1.400	1.885	1.400	2.175 3.690	1.400	2.175 3.690			
1.450	1.955	1.450	2.260 3.830	1.450	2.260 3.830			
1.500	2.030	1.500	2.340 3.970	1.500	2.340 3.970			